

# BACKUP CAMERA SYSTEM WITH REPLACEMENT MIRROR MONITOR RVS - 770718

REAR VIEW  
**SAFETY**  
REVERSE WITH CONFIDENCE™



This system is complete with a color 4.3" TFT-LCD Mirror Monitor which attaches to the windshield in the vehicle, replacing the existing rear view mirror. The system has mirror image capability with distance grid lines, a power harness with two camera inputs, a 130° CCD camera with 50 foot infra-red night vision and all the wires, connectors and mounts you will need. The distance grid lines with this system are adjustable which means that regardless where you mount the camera, the grid lines will display correctly. The system is completely weatherproof with an IP69K rating, strong and reliable, shock resistant, with a 20G vibration rating (highest in the industry). It comes with a full year warranty.



# BACKUP CAMERA SYSTEM WITH REPLACEMENT MIRROR MONITOR

**REAR VIEW  
SAFETY**  
REVERSE WITH CONFIDENCE™

## RVS - 770718

- COMPLETELY WEATHERPROOF WITH AN IP69K RATING
- OEM FACTORY - LIKE MIRROR MONITOR REPLACES EXISTING REAR VIEW MIRROR
- SUPER BRIGHT 4.3" TFT LCD COLOR SCREEN
- 1/3" SHARP® COLOR CCD, 410K PIXELS, 2.5MM WIDE LENS WITH 130° ANGLE
- SHOCK RESISTANT WITH A 20G VIBRATION AND A 100G IMPACT RATING



### MONITOR

SCREEN SIZE	4.3"
DOT RESOLUTION	480 X 3 (RGB) X 272
DISPLAY FORMAT	16:9
DISPLAY BRIGHTNESS	400
VIEWING ANGLE	U&D: 100°, L&R: 120°
VIDEO INPUT	2 CHANNEL
VIDEO SOURCE	1VP - P, 75 Ω
POWER SUPPLY	DC 9V - 32V
POWER CONSUMPTION	5W
OPERATING TEMPERATURE	-20 °C ~ +75 °C
VIDEO SYSTEM	AUTO NTSC / PAL
OVERALL DIMENSIONS	10.55" (L) X 3.15" (H) X 1" (D)
WEIGHT	800G
VIBRATION RATING	5G
SYNC SYSTEM	INTERNAL

### CAMERA

CAMERA	1/3" SHARP® COLOR CCD
PICTURE ELEMENTS	410,000 PIXELS
GAMMA CORRECTION	R=0.45 TO 1.0
IMAGE SENSOR	620 TV LINES
PIXELS	PAL: 752 (H) X 582 (V) NTSC: 811 (H) X 507 (V)
LENS	F=2.5MM
VIEW ANGLE	130°
WATERPROOF RATING	IP69K
SYNC SYSTEM	INTERNAL SYNCHRONIZATION
INFRA-RED DISTANCE	50 FEET (18 INFRARED)
USABLE ILLUMINATION	0 LUX (IR ON)
POWER SOURCE	DC 9V-32V
S/N RATIO	MORE THAN 48DB
ELECTRONIC IRIS	1/50, 160-1/100,000SEC
VIDEO OUTPUT	1VP - P, 75 Ω
IR SWITCH CONTROL	ACDS AUTOMATIC CONTROL
VIBRATION AND SHOCK RATING	20G / 100G
OPERATING TEMPERATURE	-40°C ~ +70°C / RH 95% MAX
STORAGE TEMPERATURE	-40°C ~ +85°C / RH 95% MAX